

List of pages in this Trip Kit

Trip Kit Index

Airport Information For TNCM

Terminal Charts For TNCM

Revision Letter For Cycle 11-2024

Change Notices

Notebook

General Information

Location: ST MAARTEN I ANT
ICAO/IATA: TNCM / SXM
Lat/Long: N18° 02.46', W063° 06.54'
Elevation: 14 ft

Airport Use: Public
Daylight Savings: Not Observed
UTC Conversion: +4:00 = UTC
Magnetic Variation: 14.0° W

Fuel Types: 100 Octane (LL), 100-130 Octane, Jet A, Jet A-1
Customs: Yes
Airport Type: IFR
Landing Fee: Yes
Control Tower: Yes
Jet Start Unit: No
LLWS Alert: No
Beacon: Yes

Sunrise: 0936 Z
Sunset: 2245 Z

Runway Information

Runway: 10
Length x Width: 7546 ft x 148 ft
Surface Type: asphalt
TDZ-Elev: 12 ft
Lighting: Edge
Displaced Threshold: 328 ft

Runway: 28
Length x Width: 7546 ft x 148 ft
Surface Type: asphalt
TDZ-Elev: 9 ft
Lighting: Edge

Communication Information

ATIS: 127.650
Juliana Tower: 118.700
Juliana Clearance Delivery: 121.650
Juliana Approach: 118.700 Secondary
Juliana Approach: 128.950


**ST MAARTEN I,
NETH ANTILLES
(PHILIPSBURG)**



28 DEC 18 (10-2) Eff 3 Jan STAR

**TNCM/SXM
PRINCESS JULIANA INTL**

*ATIS 127.65	Apt Elev 14
Alt Set: hPa Trans level: FL65 RADAR required.	
ULUBA 1 ARRIVAL [ULUBA 1]	
ROUTING	
FROM	
DANDE	Track 040°.
ELOPO	Track 305°.
GOUDA	Track 087°.
MNOLO	Track 260°.
SLUGO	Track 160°.
TRNKY	Track 225°.
ZPATA	Track 325°.
LANDING	
EXPECT vectors to execute the VOR Z RWY 10 approach straight-in.	
Direct distance to ULUBA from: DANDE 37.3 NM ELOPO 47.5 NM GOUDA 22.0 NM MNOLO 34.2 NM SLUGO 31.0 NM TRNKY 24.9 NM ZPATA 41.7 NM	



CHANGES: TIKAL waypoint renamed ZPATA.

© JEPPESEN, 2018 - ALL RIGHTS RESERVED.

**ST MAARTEN I,
NETH ANTILLES
(PHILIPSBURG)**

TNCM/SXM

PRINCESS JULIANA INTL

24 AUG 18

10-3




RNAV SID

Apt Elev
14

Trans alt: 5000

**BOPAT 2 [BOPAT2]
RWY 10 RNAV (GNSS) DEPARTURE**



This SID requires a minimum 1200 ceiling and 2.8 NM visibility to see and avoid the mountain 2.8 NM EAST of take-off end RWY 10. Operators will maneuver visually over lower terrain.

CLOSE-IN OBSTACLES

- A. 602 hazard beacon 6227 from DER, 620 LEFT of centerline.
- B. 1118 hazard beacon 9224 from DER, 2044 RIGHT of centerline.

INITIAL CLIMB

Routing instructions may be superseded by RADAR vectors. As soon as practicable turn RIGHT.

VIA	ROUTING
DANDE	Climb direct BOPAT. Cross BOPAT at or above 4000, if unable advise ATC. Then direct DANDE.
GOUDA	Climb direct BOPAT. Cross BOPAT at or above 4000, if unable advise ATC. Turn RIGHT direct GOUDA.
JUICE	Climb direct BOPAT. Cross BOPAT at or above 4000, if unable advise ATC. Turn RIGHT direct JUICE.

**ST MAARTEN I,
NETH ANTILLES
(PHILIPSBURG)**
JEPPESEN
28 DEC 18 (10-3A) Eff 3 Jan SID


**TNCM/SXM
PRINCESS JULIANA INTL**

Apt Elev 14	Trans alti: 5000 DME required.
JULIANA 2 (JULNA2) RWY 10 DEPARTURE	
INITIAL CLIMB As soon as practicable turn RIGHT.	
TRANSITIONS	
DANDE	Intercept/track PJM R166. Cross D10.0 PJM at or above 4000, if unable advise ATC. Turn RIGHT on D12.0 Arc PJM. Turn LEFT on PJM R237 to DANDE.
ESVAN	Intercept/track PJM R166. Cross D10.0 PJM at or above 4000, if unable advise ATC. To ESVAN.
GOUDA	Intercept/track PJM R166. Cross D10.0 PJM at or above 4000, if unable advise ATC. Turn RIGHT on D12.0 Arc PJM. Crossing PJM R237 track 325°. Turn LEFT on PJM R271 to GOUDA.
JUICE	Intercept/track PJM R166. Cross D10.0 PJM at or above 4000, if unable advise ATC. Turn RIGHT on D12.0 Arc PJM. Crossing PJM R237 track 325°. Turn LEFT on PJM R292 to JUICE.
MNOLO	Intercept/track PJM R166. Cross D10.0 PJM at or above 4000, if unable advise ATC. Turn LEFT on D12.0 Arc PJM. Turn RIGHT on PJM R059 to MNOLO.
ONBED	Intercept/track PJM R166. Cross D10.0 PJM at or above 4000, if unable advise ATC. Turn LEFT on D12.0 Arc PJM. Turn RIGHT on PJM R138 to ONBED.
TRNKY	Intercept/track PJM R166. Cross D10.0 PJM at or above 4000, if unable advise ATC. Turn LEFT on D12.0 Arc PJM. Turn RIGHT on PJM R004 to TRNKY.

This SID requires a minimum 1200 ceiling and 2.8 NM visibility to see and avoid the mountain 2.8 NM EAST of take-off end RWY 10. Operators will maneuver visually over lower terrain.

CLOSE-IN OBSTACLES
A. 602 hazard beacon 6227 from DER, 620 LEFT of centerline.
B. 1118 hazard beacon 9224 from DER, 2044 RIGHT of centerline.

Direct distance from PJM VOR to:
DANDE 44.7
ESVAN 30.0
GOUDA 32.0
JUICE 31.8
MNOLO 25.8
ONBED 20.0
TRNKY 23.2



**ST MAARTEN I,
NETH ANTILLES
(PHILIPSBURG)**

JEPPESEN
28 DEC 18 (10-3B) Eff 3 Jan

**TNCM/SXM
PRINCESS JULIANA INTL**

RNAV SID

Apt Elev
14
Trans alt: 5000

**MODOR 2 [MODOR2]
RNAV (GNSS) DEPARTURE**


INITIAL CLIMB
Routing instructions may be superseded by RADAR vectors.
As soon as practicable turn RIGHT.

VIA	ROUTING
DANDE	Climb direct MODOR. Cross MODOR at or above 4000, if unable advise ATC, turn RIGHT direct DANDE.
ELOPO	Climb direct MODOR. Cross MODOR at or above 4000, if unable advise ATC, turn LEFT direct ELOPO.
GOUDA	Climb direct MODOR. Cross MODOR at or above 4000, if unable advise ATC, turn RIGHT direct GOUDA.
JUICE	Climb direct MODOR. Cross MODOR at or above 4000, if unable advise ATC, turn RIGHT direct JUICE.
MNOLO	Climb direct MODOR. Cross MODOR at or above 4000, if unable advise ATC, turn LEFT direct MNOLO.
TRNKY	Climb direct MODOR. Cross MODOR at or above 4000, if unable advise ATC, turn LEFT direct TRNKY.
ZPATA	Climb direct MODOR. Cross MODOR at or above 4000, if unable advise ATC, turn LEFT direct ZPATA.

This SID requires a minimum 1200 ceiling and 2.8 NM visibility to see and avoid the mountain 2.8 NM EAST of take-off end RWY 10. Operators will maneuver visually over lower terrain.

CLOSE-IN OBSTACLES
A. 602 hazard beacon 6227 from DER, 620 LEFT of centerline.
B. 1118 hazard beacon 9224 from DER, 2044 RIGHT of centerline.

Direct distance from Runway 10 beginning of TORA to: MODOR 10.1 NM



ST MAARTEN I,
NETH ANTILLES
(PHILIPSBURG)




28 DEC 18 10-3C Eff 3 Jan

SID

Apt Elev
14
Trans alt: 5000
RADAR required.

MULLET 2 (MULLT2)
RWY 10 DEPARTURE

TNCM/SXM
PRINCESS JULIANA INTL



TRANSITIONS	
DANDE	Track 230° to D10.0 PJM, cross D10.0 PJM at or above 4000, if unable advise ATC, turn RIGHT track 250°, intercept A-516.
ELOPO	Track 230° to D10.0 PJM, cross D10.0 PJM at or above 4000, if unable advise ATC, turn LEFT track 115°, intercept B-520.
GOUDA	Track 230° to D10.0 PJM, cross D10.0 PJM at or above 4000, if unable advise ATC, turn RIGHT track 315°, intercept R-760.
JUICE	Track 230° to D10.0 PJM, cross D10.0 PJM at or above 4000, if unable advise ATC, turn RIGHT track 315°, intercept B-520.
ZPATA	Track 230° to D10.0 PJM, cross D10.0 PJM at or above 4000, if unable advise ATC, turn LEFT track 115°, intercept A-517.

INITIAL CLIMB
Routing instructions may be superseded by RADAR vectors. As soon as practicable turn RIGHT.

CLOSE-IN OBSTACLES
A. 602 hazard beacon 6227 from DER, 670 LEFT of centerline.
B. 1118 hazard beacon 9224 from DER, 2044 RIGHT of centerline.

This SID requires a minimum 1200 ceiling and 2.8 NM visibility to see and avoid the mountain 2.8 NM EAST of take-off end RWY 10. Operators will maneuver visually over lower terrain.


**ST MAARTEN I,
NETH ANTILLES
(PHILIPSBURG)**



28 DEC 18 (10-3D) EFF 3 Jan SID

**TNCM/SXM
PRINCESS JULIANA INTL**

Apt Elev 14	Trans alt: 5000 RADAR required.
PELICAN 2 (PELCN2) RWY 10 DEPARTURE	
INITIAL CLIMB	
Routing instructions may be superseded by RADAR vectors. As soon as practicable turn RIGHT.	
TRANSITIONS	
DANDE	Track 180° to D10.0 PJM, cross D10.0 PJM at or above 4000, if unable advise ATC, turn RIGHT track 270°, intercept A-516.
ELOPO	Track 180° to D10.0 PJM, cross D10.0 PJM at or above 4000, if unable advise ATC, turn LEFT track 115°, intercept B-520.
GOUDA	Track 180° to D10.0 PJM, cross D10.0 PJM at or above 4000, if unable advise ATC, turn RIGHT track 315°, intercept R-760.
JUICE	Track 180° to D10.0 PJM, cross D10.0 PJM at or above 4000, if unable advise ATC, turn RIGHT track 315°, intercept B-520.
MNOLO	Track 180° to D10.0 PJM, cross D10.0 PJM at or above 4000, if unable advise ATC, turn LEFT track 020°, intercept A-516.
TRNKY	Track 180° to D10.0 PJM, cross D10.0 PJM at or above 4000, if unable advise ATC, turn LEFT direct PJM VOR, intercept L-461.
ZPATA	Track 180° to D10.0 PJM, cross D10.0 PJM at or above 4000, if unable advise ATC, turn LEFT intercept A-517.
This SID requires a minimum 1200 ceiling and 2.8 NM visibility to see and avoid the mountain 2.8 NM EAST of take-off end RWY 10. Operators will maneuver visually over lower terrain.	
CLOSE-IN OBSTACLES	
A. 602 hazard beacon 6227 from DER, 620 LEFT of centerline.	
B. 1118 hazard beacon 9224 from DER, 2044 RIGHT of centerline.	



TNCM/SXM

JEPPesen ST MAARTEN I, NETH ANTILLES

Apt Elev 14'

(PHILIPSBURG)

N18 02.5 W063 06.5


12 JUN 20

10-9

PRINCESS JULIANA INTL

*ATIS	*JULIANA Delivery	*Tower
127.65	121.65	118.7

Traffic entering, transiting or operating within TMA contact Juliana Approach on 128.95.




All landing helicopter traffic intending to park at the H Apron shall proceed along the rwy centerline, enter Twy H and follow the taxi guidance lines to the designated parking stand.

Maximum helicopter rotor size allowed is 33' (10m) in diameter.

All helicopter traffic intending to depart from the H Apron must follow the taxi guidance lines and exit Twy H onto the active rwy, then depart along the rwy centerline for the rwy in use.

Helicopters shall avoid built up areas in as far as practical.



PARKING SPOT COORDINATES	
SPOT NO.	COORDINATES
A1	N18 02.6 W063 06.9
A2, A3	N18 02.6 W063 06.8
A4	N18 02.6 W063 06.7
B1, B2	N18 02.6 W063 06.9
B3	N18 02.5 W063 07.0
B4	N18 02.5 W063 06.9
B5	N18 02.5 W063 06.8
C1	N18 02.5 W063 06.7
C2	N18 02.6 W063 06.7
C3 thru C10	N18 02.5 W063 06.7
C11, C12	N18 02.5 W063 06.6
H Apron HELI PARKING COORDINATES	
SPOT NO.	COORDINATES
H1	N18 02.5 W063 05.9
H2, H3	N18 02.5 W063 05.8

TNCM/SXM



ST MAARTEN I, NETH ANTILLES

(PHILIPSBURG)

12 JUN 20

10-9A

PRINCESS JULIANA INTL

GENERAL

All landing aircraft utilizing the intermediate turning bay Rwy 10 shall make their turn to the RIGHT to avoid any injury to persons and/or damage to property south of the RWY.

Heavy aircraft are not permitted to turn at the intermediate turning bay Rwy 10 and shall proceed to the Rwy end and follow the turn guidance markings to make a RIGHT 180° turn.

All traffic intending to depart from Rwy 10 and requiring the use of the pre-threshold area are permitted to taxi across the red inset lights on Rwy 10 displaced threshold during backtracking.

Birds in vicinity of the airport.

Righthand traffic circuit for Rwy 10, lefthand circuit for Rwy 28.

ADDITIONAL RUNWAY INFORMATION

RWY	Landing Guidance	USABLE LENGTHS		TAKE-OFF	WIDTH
		Threshold	Glide Slope		
10	MIRL PAPI (angle 3.0°)	7218' 2200m		7218' 2200m	150' 46m
① 28	MIRL				

① Landing Rwy 28 at night prohibited, VMC by day.

Std		TAKE-OFF			
RL & RCLM	RL	RL or RCLM	Adequate Vis Ref		
DAY	NIGHT	DAY	DAY	NIGHT	
R300m		R400m	R/V500m	NA	

TNCM/SXM

JEPPESEN ST MAARTEN I, NETH ANTILLES
 (PHILIPSBURG)
 PRINCESS JULIANA INTL

1 DEC 06

(10-9D)

VISUAL DOCKING GUIDANCE SYSTEMS

1. INTRODUCTION

The Safedock Docking Guidance System (DGS) is an automated "parking aid" system designed to safely guide the aircraft into gate to its assigned stop-position. It accomplishes this by actively tracking the aircraft while providing the pilot real-time visual feedback of "distance-to-go" and azimuth guidance in relation to the centerline and stop-position.

2. SAFETY PROCEDURES

2.2 GENERAL WARNING

The DGS has built-in features of self-diagnostics and gate area scanning checks to inform the aircraft pilot of problems that could affect the safety of the docking procedure. Refer to "section 4. ABNORMAL CONDITIONS" for further details on these items.

If the pilot is unsure of the information being shown on the DGS Display unit, the aircraft **SHOULD BE STOPPED IMMEDIATELY UNTIL** further information for clearance **HAS BEEN OBTAINED**.

2.2 ITEMS TO CHECK BEFORE ENTERING THE STAND AREA

Although the DGS has built-in features of self-diagnostics and gate area scanning checks, the pilot should always use their judgement of safety should there be any items in the "obstacle free" area not captured by the DGS. In general, the aircraft should be stopped prior to further entry into the gate area if there is a presence of any object posing a question to the safety of the aircraft or personnel on the ground.

Upon entry to the gate area, the pilot should make a quick visual check of the gate area and verify that the DGS is displaying the vertical running arrows and correct aircraft type. If there is any concern in these checks, the aircraft should be stopped until the situation is corrected or manual guidance is provided. During the aircraft docking, the pilot should follow the guidance of the DGS while staying alert for any items within his view posing a danger to the aircraft or personnel on the ground.

GENERAL PRECAUTIONS:

- THE PILOT SHALL NOT ENTER THE GATE AREA, UNLESS THE DOCKING SYSTEM IS SHOWING THE VERTICAL RUNNING ARROWS.
- THE PILOT SHALL NOT ENTER THE STAND AREA UNLESS THE AIRCRAFT TYPE AND ANY OTHER DISPLAYED INFORMATION IS CORRECT FOR THE AIRCRAFT THEY ARE DOCKING.
- THE PILOT MUST NOT PROCEED BEYOND THE BOARDING BRIDGE CAB, UNLESS THESE ARROWS HAVE BEEN REPLACED BY THE "CLOSING RATE BAR".

2.3 THE SBU MESSAGE


The message STOP SBU means that docking has been interrupted due to an unexpected error or hardware malfunction and has to be resumed by manual guidance. **DO NOT RESUME DOCKING UNDER DGS-GUIDANCE UNDER THIS CONDITION.**

3. AIRCRAFT DOCKING PROCEDURE

The following section is a detailed step-by-step approach to the stages of the docking routine indicating the typical events from start to completion.

3.1 START OF DOCKING (SELF-TEST)

Upon activating the DGS for aircraft docking, a self-test and calibration check is performed to confirm docking accuracy. During this time, the display will show "WAIT".




3.2 CAPTURE (INCOMING AIRCRAFT)

The rolling arrows indicate that the SAFEDOCK is searching the gate area looking to "capture" the arriving aircraft.

Check that the correct aircraft and sub-type are displayed. If not the docking may result in an ID-fail. Following this, the pilot should proceed into the gate area following the correct lead-in line or centerline.

DO NOT PROCEED PAST THE BOARDING BRIDGE CAB IF THE ROLLING ARROWS ARE NOT REPLACED BY THE "CLOSING RATE BAR". ALSO, KEEP AWARE OF ANY VISIBLE ITEMS POSING A DANGER TO THE SAFETY OF THE AIRCRAFT OR PERSONNEL ON THE GROUND.




VISUAL DOCKING GUIDANCE SYSTEMS

3.3 TRACKING

When the DGS "captures" the approaching aircraft, the rolling arrows are replaced by a "yellow" closing rate bar". At this point, the DGS has captured the aircraft and is actively tracking it. The DGS is also in the process of verifying the approaching aircraft against that selected (as shown in the display).

A flashing RED arrow provides azimuth guidance and indicates the direction the pilot should steer the aircraft to the centerline.

The "closing rate bar" consists of a centerline indicator showing the aircraft in relation to the target stop-position.



3.4 CLOSING RATE

Digital countdown begins when the aircraft is 12 meters (or 40 feet) from its stop position. When the aircraft is within this distance, the "distance-to-go" closing rate indicator decreases by about one LED-row per 1.6 foot or half meter of movement.

Digital countdown resolution:

20 to 2 meters	1 meters	40 to 8 feet	4 feet
2 meters to STOP	0.2 meters	8 feet to STOP	1 foot

The example shows the B747 aircraft 10m from the stop-position slightly off-center to the left.



3.5 ALIGNED TO CENTER

When aligned to center, the RED direction arrows disappear indicating the aircraft is on center.

The example shows the B747 aircraft 8m from the stop-position and on-center.



3.6 SLOW DOWN

If the aircraft is approaching faster than the accepted speed, the system will show SLOW DOWN as a warning to the pilot.

The example now shows the B747 aircraft about 8m from the stop-position and still on-center yet needing to slow down.



3.7 AZIMUTH GUIDANCE

Centerline guidance continues to the stop-position.

The example shows the B747 aircraft 4m from the stop-position, slightly off-center to the right.



3.8 STOP-POSITION REACHED

When the aircraft reaches its assigned stop-position, the display will show STOP with RED lights to each side.



3.9 DOCKING COMPLETED

After the aircraft is completely stopped, the OK message will be displayed.



3.10 OVERTHOOT (TOO FAR)

If the aircraft overshoots the stop-position, a TOO FAR will be displayed.

Note: The overshoot condition is usually triggered by the aircraft going more than 0.5m past the target stop-position. This may or may not create a concern for the boarding bridge to accommodate the overshoot position. The ground crew will be alerted to the situation by this message and then determine if the aircraft needs to be pushed back.



TNCM/SXM

JEPPesen ST MAARTEN I, NETH ANTILLES

1 DEC 06

10-9F

(PHILIPSBURG)

PRINCESS JULIANA INTL

VISUAL DOCKING GUIDANCE SYSTEMS

3.11 CHOCKS ON MESSAGE

The "Chocks On" is displayed to indicate that the chocks have been set in place to the aircraft wheels. This feature is available via button press on the Operator's Panel to provide or supplement the ground operator's responsibility to provide the status message to the pilot.



3.12 STOP SHORT

If the aircraft is stopped short and at a standstill but has not reached the intended stop position, the message STOP OK will be shown after a while.



4. ABNORMAL CONDITIONS

If an object is blocking the view from the SAFEDOCK DGS laser-scanning unit toward the stop position of the selected aircraft type, the system will be unable to perform the docking procedure. When an object is detected between the laser scanning unit and the stop position for at least ten seconds, the DGS will halt the docking procedure and display a GATE BLOCK warning message. When the blocking object is removed, the docking procedure will be resumed. The same applies with an object detected in the "apron scan" area whereas the DGS will display an "APRON BLOCK" warning message. Note that the "apron scan" feature only covers the pilot's blind spot area when the aircraft requires a right turn into the gate. See further details later in this section for more info on this.

If an unrecoverable error occurs during a docking procedure, a SBU (Safety Back Up) condition exists. In this case an alternate method to guide aircraft to the stop position must be used, as the docking procedure cannot be completed. SBU stop conditions are:

- (a) A hardware failure.
- (b) Aircraft more than 3.5 degrees off centerline and less than 2m (6.5ft) to the stop-position
- (c) View from Laser scanning unit to aircraft blocked with less than 2m (6.5ft) to the stop-position.

WARNING: An object must never be placed in front of the DGS unit and closer than 1.5 meters (or 5 feet) to the laser window. Such an object would violate proper docking performance!

Other abnormal or non-typical conditions that may occur are as follows:

4.1 WAIT

The WAIT message is displayed for various reasons and may be followed with further info. In general, it is an indication to the pilot that the DGS is not yet ready to guide or continue guiding the aircraft into the gate. The reasons may vary from startup self-testing, lost track of the aircraft, or large obstacles or personnel in the critical docking area or obstacle free zone. Basically, something that may compromise the docking or a safety concern.

When the problem is resolved or the blocking object has moved from the critical docking area, docking may continue. The DGS display must also show the "closing rate" bar and that it is back in docking mode AND tracking the aircraft.

THE PILOT MUST NOT PROCEED BEYOND THE BOARDING BRIDGE CAB UNLESS THE "WAIT" MESSAGE HAS BEEN REMOVED AND THE DGS INDICATES IT IS TRACKING THE AIRCRAFT INTO THE GATE AREA.



4.2 BRIDGE NOT IN POSITION

The "BR IN" message occurs when the Passenger Boarding Bridge (PBB) is interlocked to the DGS and is NOT safely stowed or parked in the proper parking position (or a defect in the wiring).

This message with the red-LEDs is indication to the pilot that aircraft docking MUST wait until ground personnel move the PBB into safe position away from the critical docking area.

THE PILOT MUST NOT PROCEED BEYOND THE BOARDING BRIDGE CAB UNLESS THE "BR IN" MESSAGE HAS BEEN REMOVED AND THE DGS INDICATES IT IS TRACKING THE AIRCRAFT INTO THE GATE AREA.



TNCM/SXM

JEPPESEN ST MAARTEN I, NETH ANTILLES

1 DEC 06 (10-9G)

(PHILIPSBURG)

PRINCESS JULIANA INTL

VISUAL DOCKING GUIDANCE SYSTEMS

4.3 BAD WEATHER CONDITION (DOWN-GRADE)

During heavy fog, rain or snow, or any low visibility condition, the docking system goes into downgrade mode.

When operating at this mode, the display will deactivate the floating arrows and alternate between 'DOWN GRADE' and aircraft type. The DGS will continue operation but with reduced aircraft slow-down speed.

This message will be replaced by the closing rate bar, as soon as the system detects and captures the approaching aircraft.

THE PILOT MUST NOT PROCEED BEYOND THE BRIDGE CAB UNLESS THE "DOWN GRADE" TEXT HAS BEEN REMOVED AND THE DGS INDICATES IT IS TRACKING THE AIRCRAFT INTO THE GATE AREA.



4.4 AIRCRAFT VERIFICATION FAILURE

After capture of the aircraft, the DGS checks its geometry against a stored profile. If, for any reason, aircraft verification is not confirmed at 12 meters (or 40 feet) before the target stop-position, the display will show STOP followed by ID FAIL (alternating on the upper row of the display).

If the DGS is re-activated for the same aircraft type, docking can resume without aircraft verification. Note that such re-activation should be done only after the ground crew has verified the correct aircraft type.

THE PILOT MUST NOT PROCEED BEYOND THE BOARDING BRIDGE CAB WITHOUT MANUAL GUIDANCE, UNLESS THE DOCKING HAS BEEN RE-ACTIVATED AND THE DGS INDICATES IT IS TRACKING THE AIRCRAFT INTO THE GATE AREA.



4.5 GATE BLOCKED

If an object is found blocking the view from the DGS to the planned stop position for the aircraft, the docking procedure will be halted with a GATE BLOCK message. The docking procedure will resume as soon as the blocking object has been removed.

The "Gate Block" area covers the general scanning area of the approaching aircraft and where the aircraft body will be when parked as well as the area between the DGS and those points. In general, the message is provoked by large obstacles interfering this scanning area. This feature does not look for smaller interfering items on the apron.

THE PILOT MUST NOT PROCEED INTO THE GATE AREA WITHOUT MANUAL GUIDANCE, UNLESS THE "WAIT/GATE/BLOCK" MESSAGE HAS BEEN REMOVED AND THE DGS INDICATES IT IS TRACKING THE AIRCRAFT INTO THE GATE AREA.



4.6 VIEW BLOCKED

If the view towards the approaching aircraft is hindered, for instance by dirt on the window, the DGS will report a View Blocked condition. If the system is able to see the aircraft through the dirty window, the message will be replaced with a closing rate display.

The difference between the "View Block" and the "Gate Block" feature is that the "View Block" feature looks for interference within 2m of distance from the laser and the "Gate Block" feature looks for interference past this distance.

THE PILOT MUST NOT PROCEED BEYOND THE BOARDING BRIDGE CAB WITHOUT MANUAL GUIDANCE, UNLESS THE WAIT MESSAGE HAS BEEN REMOVED AND THE DGS INDICATES IT IS AGAIN TRACKING THE AIRCRAFT INTO THE GATE AREA.



4.7 TOO FAST

If the aircraft approaches with a speed higher than the docking system can handle, the message STOP (with red squares) and TOO FAST will be displayed.

The aircraft docking must be re-started or the docking procedure completed by manual guidance.

THE PILOT MUST NOT PROCEED BEYOND THE BOARDING BRIDGE CAB WITHOUT MANUAL GUIDANCE, UNLESS THE DOCKING HAS BEEN RE-ACTIVATED AND THE DGS INDICATES IT IS TRACKING THE AIRCRAFT INTO THE GATE AREA.



TNCM/SXM

JEPPESEN ST MAARTEN I, NETH ANTILLES

1 DEC 06 (10-9H)

(PHILIPSBURG)

PRINCESS JULIANA INTL

VISUAL DOCKING GUIDANCE SYSTEMS

4.8 ANOMALOUS ERROR, SBU-STOP

Any anomalous or unrecoverable error during the docking procedure will generate a SBU condition. A manual backup procedure must be used for docking guidance.

Note: An SBU-Stop may be followed by another error related to a hardware failure or other anomalous event.

THE PILOT MUST FOLLOW MANUAL GUIDANCE INTO THE GATE WHEN THE DGS DISPLAY IS IN THIS CONDITION.



4.9 ERROR CONDITION

Any error that occurs during the DGS operation will generate an ERROR message with an error code in the main display. Errors that occur during aircraft docking may be proceeded with an "SBU" message.

THE PILOT MUST FOLLOW MANUAL GUIDANCE INTO THE GATE WHEN THE DGS DISPLAY IS IN THIS CONDITION.



4.10 EMERGENCY STOP

If the Emergency Stop button is pressed (by the ground operator), the display will show STOP with RED lights to each side.

The ground crew may activate this button to indicate a dangerous condition that requires aircraft motion to STOP and NOT continue its approach into the gate.


THE PILOT SHOULD STOP THE AIRCRAFT AT ANY TIME THE STOP MESSAGE IS DISPLAYED DURING DGS DOCKING GUIDANCE THEN FOLLOW MANUAL GUIDANCE.



4.11 NON-OPERATIONAL CONDITION

Should there be a hardware failure that interferes with the DGS ability to operate, the display will go blank with RED lights to each side. In such cases, the DGS cannot be used until the hardware failure has been resolved.

THE PILOT MUST FOLLOW MANUAL GUIDANCE INTO THE GATE WHEN THE DGS DISPLAY IS IN THIS CONDITION.



4.12 NO POWER (OR POWER FAILURE)

When the DGS is powered-Off, or in the case of a power failure, the display will be shown as completely black. Until power is restored, any aircraft shall be marshalled-in or towed-in to the gate.

THE PILOT MUST FOLLOW MANUAL GUIDANCE INTO THE GATE WHEN THE DGS DISPLAY IS IN THIS CONDITION.





TNCM/SXM

JEPPESSEN ST MAARTEN I, NETH ANTILLES
(PHILIPSBURG)

PRINCESS JULIANA INTL 12 JUN 20 (12-1)

RNAV (GNSS) Rwy 10

*ATIS 127.65		*JULIANA Approach 128.95		*JULIANA Tower 118.7	
RNAV	Final Apch Crs 096°	LESOR 1700' (1686')	LNAV DA/MDA(H) (CONDITIONAL) 700' (686')	Apt Elev 14'	4100 MSA ARP
MISSED APCH: Climbing RIGHT turn to 4000' direct ONBED and hold, or as directed by ATC.					
Alt Set: hPa		Rwy Elev: 0 hPa		Trans level: FL 65	
1. GNSS required. 2. DME/DME not authorized.					



Gnd speed-Kts	70	90	100	120	140	160	PAPI	4000'	D → ONBED
Descent Angle	3.00°	372	478	531	637	849			
MAP at MAPON									

PANS OPS	Sid	STRAIGHT-IN LANDING			
		1 LNAV CDFA 2 DA/MDA(H) 700' (686')		LNAV CDFA 2 DA/MDA(H) 770' (756')	
	A	R1500m		R1500m	
	B	R2400m		R2400m	

1 Missed Approach restricted to a maximum of 205 KT until established direct ONBED.
2 VNAV DA(H) in lieu of MDA(H) depends on operator policy.

TNCM/SXM

JEPPESEN ST MAARTEN I, NETH ANTILLES
(PHILIPSBURG)



1 OCT 21 **13-1** Eff 7 Oct

PRINCESS JULIANA INTL

CAT C & D

VOR X Rwy 10

*ATIS 127.65		*JULIANA Approach 128.95		*JULIANA Tower 118.7	
VOR PJM 113.0	Final Apch Crs 096°	No FAF	DA/MDA(H) 1040' (1026')	Apt Elev 14'	<p>2600 090° 4100 360° MSA PJM VOR</p>
MISSED APCH: Track 180° climbing to 4000', passing 2600' turn LEFT direct PJM VOR and hold.					
Alt Set: hPa	Apt Elev: 1 hPa	Trans level: FL 65	Trans alt: 5000'		
Timing not authorized for defining Missed Approach Point.					



Gnd speed-Kts	70	90	100	120	140	160	PAPI	4000' on 180°
Descent Angle 3.00°	372	478	531	637	743	849		
MAP at VOR								

PANS OPS	Std	STRAIGHT-IN LANDING CDFA 1 DA/MDA(H) 1040' (1026')	CIRCLE-TO-LAND
	A	NOT APPLICABLE	NOT APPLICABLE
	B	NOT APPLICABLE	
	C	R2400m	
D			

1 VNAV DA(H) in lieu of MDA(H) depends on operator policy.

TNCM/SXM

JEPPESSEN ST MAARTEN I, NETH ANTILLES



1 OCT 21 **13-2 Eff 7 Oct**

(PHILIPSBURG)

PRINCESS JULIANA INTL

VOR Z Rwy 10

*ATIS 127.65		*JULIANA Approach 128.95		*JULIANA Tower 118.7	
VOR PJM 113.0	Final Apch Crs 096°	DEBIR 1600' (1586')	DA/MDA(H) (CONDITIONAL) 500' (486')	Apt Elev 14'	
<p>MISSED APCH: Track 180° climbing to 4000', passing 2600' within 10 DME turn LEFT direct PJM VOR and hold.</p>					
Alt Set: hPa		Apt Elev: 1 hPa		Trans level: FL 65	
1. DME required.		2. Timing not authorized for defining Missed Approach Point.		MSA PJM VOR	



Gnd speed-Kts	70	90	100	120	140	160	PAPI	4000'	on 180°
Descent Angle	2.98°	369	474	527	633	738			
MAP at D2.0									

PANS OPS	Std STRAIGHT-IN LANDING		CIRCLE-TO-LAND
	CDFA	CDFA	
	1 DA/MDA(H) 500' (486')	2 DA/MDA(H) 770' (756')	
	A	R2300m	R3500m
B			
C			
D			

1 Missed Approach restricted to a maximum of 205 KIAS until tracking 180°.
2 VNAV DA(H) in lieu of MDA(H) depends on operator policy.

TNCM/SXM

JEPPESEN ST MAARTEN I, NETH ANTILLES
(PHILIPSBURG)



1 OCT 21 **13-3** Eff 7 Oct

PRINCESS JULIANA INTL

CAT A & B

VOR Y Rwy 10

*ATIS 127.65		*JULIANA Approach 128.95		*JULIANA Tower 118.7	
VOR PJM 113.0	Final Apch Crs 096°	No FAF	DA/MDA(H) 990' (976')	Apt Elev 14'	<p>2600 090° 4100 360°</p> <p>MSA PJM VOR</p>
MISSED APCH: Track 180° climbing to 4000', passing 2600' turn LEFT direct PJM VOR and hold.					
Alt Set: hPa		Apt Elev: 1 hPa		Trans level: FL 65	
Timing not authorized for defining Missed Approach Point.					



Grnd speed-Kts	70	90	100	120	140	160	PAPI	4000' ↑ on 180°
Descent Angle 3.00°	372	478	531	637	743	849		
MAP at VOR								

PANS OPS	Std	STRAIGHT-IN LANDING CDFA 1 DA/MDA(H) 990' (976')	CIRCLE-TO-LAND
	A	R1500m	NOT APPLICABLE
	B		
	C	NOT APPLICABLE	
D			

1 VNAV DA(H) in lieu of MDA(H) depends on operator policy.

Chart changes since cycle 10-2024

ADD = added chart, REV = revised chart, DEL = deleted chart.

ACT	PROCEDURE IDENT	INDEX	REV DATE	EFF DATE
-----	-----------------	-------	----------	----------

ST MAARTEN I, (PRINCESS JULIANA INTL - TNCM)

TERMINAL CHART CHANGE NOTICES

No Chart Change Notices for Airport TNCM